

METHOD, PRODUCT, AND APPARATUS FOR REQUESTING A RESOURCE FROM AN IDENTIFIER HAVING A CHARACTER IMAGE

Field of the Invention

- 5 This invention generally relates to resource location, and more specifically relates to a method, product, and apparatus for requesting a resource from an identifier having a character image.

Background of the Invention

- 10 In the same way that a street address represents a location in the physical world, a domain name can be used to represent a location on the Internet. In the physical world, one relies on both street addresses and the postal system to send information back and forth between individuals and organizations. On the Internet, one relies on the Domain Name System (DNS) to translate domain
15 names into Internet addresses.

- In general, names are thought of as discrete emblems used to establish or designate identity; addresses are thought of as emblems designating location. Domain names might seem to be unusual because they appear to be both
20 names and addresses; they both locate and identify Internet resources. Yet people's personal names, for example, establish identity, and such identifiers travel with the individual rather than changing when the person changes location. Other attributes of an individual such as handwriting, fingerprints, DNA, and face recognition may also serve to identify and help remember the
25 individuality of a person. Street addresses or geographic names, by contrast, are more static in order to establish location. Yet such addresses and geographic names also serve to identify the physical place, differentiating it from other places.

- 30 Geographic names of all kinds -- street addresses, zip codes, counties -- are in fact overlays on an unchanging numerical system of longitude and latitude,

which is a universally recognized designator and locator for a particular place on the earth's surface. In this sense, geographic names are much like Internet domain names, which are an overlay of Internet address number designations.

- 5 Name space is a set of names in which all names are unique. Address space is a set of addresses in which all addresses are unique. Image space is a set of images in which all images are unique. Names are commonly used as mnemonic devices to help remember information. For instance, names are used to remember telephone numbers, and domain names are used to remember
- 10 Internet addresses. A recent area of worldwide concern is the allocation of name space on the Internet.

The Internet is a vast computer network having many smaller networks that span the world. A network provides a distributed communicating system of computers

15 that are interconnected by various electronic communication links and computer software protocols. Because of the Internet's distributed and open network architecture, it is possible to transfer data from one computer to any other computer worldwide. In 1991, the World-Wide-Web (WWW or Web) revolutionized the way information is managed and distributed.

20 The Web is based on the concept of hypertext and a transfer method known as Hypertext Transfer Protocol (HTTP) which is designed to run primarily over a Transmission Control Protocol/Internet Protocol (TCP/IP) connection that employs a standard Internet setup. A server computer may provide the data and

25 a client computer may display or process it. TCP may then convert messages into streams of packets at the source, then reassemble them back into messages at the destination. Internet Protocol (IP) handles addressing, seeing to it that packets are routed across multiple nodes and even across multiple networks with multiple standards. HTTP protocol permits client systems

30 connected to the Internet to access independent and geographically scattered server systems also connected to the Internet.

Client side browsers, such as Netscape Navigator and/or Microsoft Internet Explorer (MSIE) provide graphical user interface (GUI) based client applications that implement the client side portion of the HTTP protocol. One format for

5 information transfer is to create documents using Hypertext Markup Language (HTML). HTML pages are made up of standard text as well as formatting codes that indicate how the page should be displayed. The client side browser reads these codes in order to display the page. A web page may be static and requires no variables to display information or link to other predetermined web

10 pages. A web page is dynamic when arguments are passed which are either hidden in the web page or entered from a client browser to supply the necessary inputs displayed on the web page. Common Gateway Interface (CGI) is a standard for running external programs from a web server. CGI specifies how to pass arguments to the executing program as part of the HTTP server request.

15 Commonly, a CGI script may take the name and value arguments from an input form of a first web page which is be used as a query to access a database server and generate an HTML web page with customized data results as output that is passed back to the client browser for display.

20 The Web is a means of accessing information on the Internet that allows a user to "surf the web" and navigate the Internet resources intuitively, without technical knowledge. The Web dispenses with command-line utilities, which typically require a user to transmit sets of commands to communicate with an Internet server. Instead, the Web is made up of millions of interconnected web pages, or

25 documents, which may be displayed on a computer monitor. Hosts running special servers provide the Web pages. Software that runs these Web servers is relatively simple and is available on a wide range of computer platforms including PC's. Equally available is a form of client software, known as a Web browser, which is used to display Web pages as well as traditional non-Web

30 files on the client system.

A network resource identifier such as a Uniform Resource Identifier (URI) is a compact string of characters for identifying an abstract or physical resource. URIs are the generic set of all names and addresses that refer to objects on the Internet. URIs that refer to objects accessed with existing protocols are known
5 as Uniform Resource Locators (URLs). A URL is the address of a file accessible on the Internet. The URL contains the name of the protocol required to access the resource, a domain name, or IP address that identifies a specific computer on the Internet, and a hierarchical description of a file location on the computer. For example the URL "http://www.example.com/index.html", where "http" is the
10 scheme or protocol, "www.example.com" is the Fully Qualified Domain Name (FQDN), and "index.html" is the filename located on the server.

Because an Internet address is a relatively long string of numbers (e.g., 31.41.59.26) that is difficult to remember, Internet users rely on domain names,
15 memorable and sometimes catchy words corresponding to these numbers, in order to use electronic mail (e-mail) and to connect to Internet sites on the Web. The Domain Name System (DNS) is a set of protocols and services on a network that allows users to utilize domain names when looking for other hosts (e.g., computers) on the network. The DNS is composed of a distributed database of
20 names. The names in the DNS database establish a logical tree structure called the domain name space. Each node or domain in the domain name space is named and may contain subdomains. Domains and subdomains are grouped into zones to allow for distributed administration of the name space.

25 There is a particular increase in articles and publications emphasizing the importance of domain name space and the perceived shortage of ".com" names. References have been made that NASA is seeking authorization for ".mars" as an extension of terrestrial geography. Speaking on the opening day of the annual Internet Society (ISOC) conference in Geneva on July 22, 1998, Vint
30 Cerf, a founding President of ISOC, said the domain name debate should also encompass ".earth" or ".mars" because that's where real-time science data is

going to travel from in the not-too-distant future. He said, "The idea is to take the interplanetary Internet design and make it a part of the infrastructure of the Mars mission."

5 Ironically that same day, an on-line Wired News article reports that Network LLC has sued Centraal Corp. for patent infringement on its Internet keyword system. The system uses plain language instead of URLs to retrieve Web addresses. The technology lets companies and site owners register simple keywords that browsers can use to access Web sites. "Chevy," for example, could be used as
10 an alias to replace the lengthier Web address "http://www.chevrolet.com". The system works using a client browser plug-in. U.S. patent 5,764,906 issued on June 9, 1998, by Edelstein et al. and assigned to Network LLC, entitled, "Universal electronic resource denotation, request and delivery system" is a system that works by users guessing a short mnemonic alias without the user
15 being required to know the Web page's URL.

A system or process is typically modeled by defining the elements or components within such a system and further defining the corresponding relationships of such elements with each other and/or the relationships of such
20 elements to other systems and their respective elements. Elements or components are most typically defined as objects having properties or functions associated with such objects. Objects are distinguished by assigning a unique identifier for each object creating an object space. Identifiers are symbols, markings, characters, names, or labels used for distinguishing, tracking, tagging,
25 coding, sorting, routing, locating, linking, and organizing any combination of objects, resources, and addresses of a given system or across multiple systems. Indicia are identifiers used for referencing objects of physical or abstract resources.

30 An identifier is static and has a persistence that usually takes the form of a name or label to help people remember and commonly agree upon the identification of

an object for a given system. In effect, for any given object space there is typically defined an associated naming system. Each naming system may include one or more namespaces. In some naming systems, identifiers may be allocated, assigned, reserved, subscribed, or registered to an object or entity
5 such as an individual or organization. Examples of such registered identifiers include Social Security Numbers (SSN), license plate numbers, Universal Product Codes (UPC), International Standard Book Numbers (ISBN), trademarks, tradenames, company names, stock symbols, broadcast station call letters, telephone numbers, domain names, keywords, FDNs, screen names,
10 user names, etc.

Each naming system has respectively originated and evolved for its own reasons, in its own way and in its own time. Identifiers take on meaning only from within its own naming system and generally remains exclusive to other
15 naming systems. In recent years, identifiers are beginning to persist across other naming systems. For instance, there is a recent correlation between telephone numbers and trademarks. During the early 1970's, as 1-800 toll free numbers were introduced, industry recognized and extended the use of mnemonics for commercial advertising and name branding. During the 1980's,
20 1-800 names were popularized to the point where brokers would buy names with the hope of selling or leasing the 1-800 names from their growing portfolio. In fact, courts have almost unanimously held that telephone mnemonics may be protected as trademarks.

25 Another cited patent that relies on a translation database to retrieve URLs and access resources. U.S. Patent 5,812,776 issued on September 22, 1998 by Gifford, entitled, "Method of providing internet pages by mapping telephone number provided by client to URL and returning the same in a redirect command by server" allows a user to access a hypertext page by providing a conventional
30 telephone number or other descriptor. The server maps such a telephone

number or descriptor to a target page identifier using a translation database and automatically directs the client to retrieve the desired page.

There are other methods for locating resources such as image recognition, for
5 example. U.S. Patent 5,680,223 issued on October 21, 1997 by Cooper, et al.,
entitled, "Method and system for labeling a document for storage, manipulation,
and retrieval" establishes a relationship between an arbitrary, image domain file
label and a computer recognizable text domain file name for the file. The
arbitrary, image domain file label facilitates the meaningful naming of a file for
10 storage when a keyboard or other typical text entry apparatus is unavailable.

Something most individuals have in common is having a face. A face with eyes,
a nose and a mouth. All faces look a little different from each other. Different
facial features help distinguish one face from another. Facial features help most
15 people recognize a face that they have seen before. Facial features in a sense
are information for people to recognize other people's face. What is surrounding
ones face is recognized also, for instance, picture a man on a sunny day in front
of a record store named "Vinyl Press" and he is wearing a blue suit and carrying
a drum. You hear an audio recording of his drum music or you see a video
20 being played on a TV screen. You see his face brighten up emotionally when a
girl playing a guitar walks by. All the information around that face mixed with the
emotion expressed in that face help in the recognition of said face.

The alphanumeric keys located on any typewriter or keyboard are used to create
25 character images. Large groups of people everyday use character images every
day to express an emotion. Character images are recognized as images to most
people that view them. A character image that reflects an emotion a human
being is feeling is called an Emoticon. Other examples of character images are,
B-1 and :-1.

30

U.S. Patent 6,064,383 issued on May 16, 2000 by Skelly, entitled, "Method and system for selecting an emotional appearance and prosody for a graphical character" enables the user to select an emotion for a graphical character and intensity of the emotion to be reflected in the appearance of the character by using an input device. For instance, Microsoft Office (a well-known word processing program) may automatically turn a colon, hyphen, close parentheses J into a happy face, J. So does AOL Instant Messenger (a well-known communication program).

U.S. Patent 6,069,622 issued on May 30, 2000 by Kurlander, entitled, "Method and system for generating comic panels" discloses how an emoticon in a communication environment can relay communication and emotion within a series of comic panels. The comic generation system receives an interaction event and generates a comic panel. Examples of interaction events include text input (e.g., a character image) by a user and selection of gestures and expressions by a user.

Character images and emoticons may also be used in Virtual Reality. A virtual environment may be generated from a programming language called, Virtual Reality Markup Language (VRML). In a virtual environment everything looks 3D and as if one is existing in it. Another virtual environment which is very popular today is the 3D gaming environment. Such games that are popular today are Quake and Dune where real people play an interactive game off or online. In a virtual environment or interactive game real people take on a graphic presence known as an avatar. Most avatars have a face. In essence a face of an avatar is almost the same as a face of an emoticon in which they both exist in a computer based environment and are used to relay emotion and a message. They are vehicles for mnemonic information to the things we humans communicate and associate with.

A character image more particularly an emoticon is different then a lot of other symbols for its ability of being scanned and recognized by a multitude of devices and formats that exist.

5 U.S. Patent 6,076,121 issued on June 13, 2000 by Levine, entitled, "Method of network addressing and translation" discloses a system and method in a telephone network for assigning a directory number to each user, and functional property code(s) to each device a user employs. The same directory number is then used to reach the user, whereby the system will automatically use the
10 functional property code of each device to reach the user's voice line, cellular line, fax line, data line or other telephone network device.

U.S. Patent 6,154,738 issued on November 28, 2000 by Call, entitled, "Methods and apparatus for disseminating product information via the internet using
15 universal product codes" receives Internet request messages containing all or part of a universal product code and returns the Internet address at which information about the identified product, or the manufacturer of that product, may be obtained.

20 This supports the need for a system that labels products on a computer network. There are other devices that can communicate on these infrastructures and recognize a symbol include, systems that work with imagery and text.

U.S. Patent 4,606,065 issued on August 12, 1986 by Beg, et al., entitled, "Image
25 processing-system" discloses an encoder that receives digital level signals and generates an indicator, in the histogram mode, of the bin to which the picture elements currently being examined belongs. In the feature-identification mode, the encoder generates an indication of whether the current picture element has the selected feature. These indications that the encoder produces will be
30 referred to in this specification as "code signals," and the general purpose of the

encoder can thus be described as being to provide a correspondence between level signals and code signals.

U.S. Patent 5,933,525 issued on August 3, 1999 by Makhoul, et al., entitled,
5 "Language-independent and segmentation-free optical character recognition system and method" discloses a unique feature extraction approach which represents two dimensional data relating to OCR as one independent variable (specifically the position within a line of text in the direction of the line) so that the same CSR technology based on HMMs can be adapted in a straightforward
10 manner to recognize optical characters.

U.S. Patent 5,909,211 issued on June 1, 1999 by Combs, et al., entitled, "Touch
pad overlay driven computer system" discloses a pressure sensitive touch pad and an overlay depicting a pattern, e.g., a typewriter keyboard, for providing
15 specific data characteristics of the pattern to a host computer and to a specific application program.

U.S. Patent 4,570,235 issued on February 11, 1986 by Kerdoncuff, et al.,
entitled, "Digital receiver of multi-frequency signals with frequency recognition
20 device" discloses digital frequency recognition device for a receiver of multi-frequency PCM signals, for the signaling between automatic telephone exchanges or between subscribers and telephone exchanges.

Other markings such as ink stamps and the like may also be used to encode
25 identifiers within images and be printed, scanned and translated to a directory location on a computer.

U.S. Patent 4,492,162 issued on January 8, 1985 by Nettesheim, et al., entitled,
"Type band ink stamp" discloses an ink stamp having movable type bands,
30 however there is no mention of using encoded identifiers to access resources.

U.S. Patent 4,571,699 issued on February 18, 1986 by Herzog, et al., entitled, "Optical mark recognition for controlling input devices, hosts, and output devices" discloses a document distribution network having one or more input work stations, a linking network with one or more nodes and one or more output work stations, is controlled by a job control sheet. The job control sheet is partitioned into a plurality of control zones. Each zone contains dedicated marked sense information for controlling the input work stations, the network nodes and the output work stations.

10 Other devices may also be adapted for use in image recognition and network resource translation.

U.S. Patent 6,166,735 issued on December 26, 2000 by Dom, et al., entitled, "Video story board user interface for selective downloading and displaying of desired portions of remote-stored video data objects" discloses a system and method for supporting video browsing over a communication network such as the Internet/World Wide Web. A GUI is provided through a client software tool such as a Web browser. A client/user selects a video data object stored at a remote server. A set of points within the object are displayed at the client's graphical user interface display, as representations, preferably thumbnail images, of the points within the object.

U.S. Patent 4,682,158 issued on July 21, 1987 by Ito, et al., entitled, "Guidance device for manipulation of machine" discloses a machine having a control panel with a plurality of keys controlling various functions. A display exhibits prompts as to the proper operation of the machine. An operator can learn the functions of the keys by manipulating them and observing the resulting prompts.

U.S. Patent 6,012,102 issued on January 4, 2000 by Shachar, et al., entitled, "System using machine-readable printed symbols created from encoded data resource specifiers to establish connection to data resource on data

communications network" discloses how access to data resources on data communications networks is simplified by encoding data resource identifiers into a machine-readable printed symbol which can be scanned into a computer-based data communications terminal. The machine-readable printed symbol can
5 be a bar code or in the form obtainable with any other printed encoding technology which encodes digital information in printed form so that it can be electronically read.

U.S. Patent 4,201,887 issued on May 6, 1980 by Burns, entitled, "Data
10 telecommunications terminal" discloses a portable, hand-held data telecommunications terminal for use with a telephone system having a memory for storing data, a signal generator for generating signals corresponding to the data, a signal coupling device connected to the signal generator for coupling the signals to the telephone system, a keyboard, a microprocessor, and a self-
15 contained power supply. Data is entered into the memory from the keyboard device so that the data is available at a future time, to be coupled to the telephone system.

U.S. Patent 5,982,303 issued on November 9, 1999 by Smith, entitled, "Method
20 for entering alpha-numeric data" discloses a method for transforming ordered pairs of keystrokes entered on a keypad with eight or more keys into a full complement of alpha-numeric characters, as might be enterable from a computer keyboard. Examples of input devices include a numeric keypad, a telephone keypad, and a "joystick." The method employs an alphabet in which each
25 character is represented by a two-stroke pictographic figure.

U.S. Patent 6,131,095 issued on October 10, 2000 by Low, et al., entitled, "Method of accessing a target entity over a communications network" discloses a telephone network and the target entity is a called party; in this case, the number
30 string comprises a dialed number and the retrieved communication data is a URI indicative of the location on the Internet of a current telephone number for the

target party, the URI once retrieve being used to access the current telephone number over the Internet for use in setting up a call to the target party.

U.S. Patent 5,869,819 issued on February 9, 1999 by Knowles, et al., entitled,
5 "Internet-based system and method for tracking objects bearing URL-encoded bar code symbols" discloses a Web-based package routing, tracking and delivering system and method that uses URL/ZIP-CODE encoded bar code symbols on parcels and packages.

10 U.S. Patent 6,101,274 issued on August 8, 2000 by Pizano, et al., entitled, "Method and apparatus for detecting and interpreting textual captions in digital video signals" discloses a computer-implemented method for the identification and interpretation of text captions in an encoded video stream of digital video signals comprises sampling by selecting frames for video analysis, decoding by
15 converting each of frames selected into a digitized color image, performing edge detection for generating a grey scale image, binarizing by converting the grey scale image into a bi-level image by means of a thresholding operation, compressing groups of consecutive pixel values in the binary image, mapping the consecutive pixel values into a binary value, and separating groups of
20 connected pixels and determining whether they are likely to be part of a text region in the image or not.

U.S. Patent 5,999,525 issued on December 7, 1999 by Krishnaswamy, et al., entitled, "Method for video telephony over a hybrid network" discloses how
25 telephone calls, data and other multimedia information including video, audio and data may be routed through a switched network which includes transfer of information across the internet. Users can transmit video, audio and data communications of designated quality over the Internet to other registered video telephony users. Users can manage more aspects of a network than previously
30 possible, and control network activities from a central site.

U.S. Patent 6,070,167 issued on May 30, 2000 by Lian, et al., entitled,
"Hierarchical method and system for object-based audiovisual descriptive
tagging of images for information retrieval, editing, and manipulation" discloses
selecting an object of interest in an image with an object-based selection
5 mechanism, generating a hierarchical data structure for the image and for
associating auxiliary information with the image, and transmitting/storing the
image and the hierarchical data structure.

U.S. Patent 6,169,555 issued on January 2, 2001 by Yamamoto, entitled,
10 "System and methods for communicating through computer animated images"
discloses a method and system for generating an animation sequence for a live
character during communication. In response to a performer's voice and other
inputs, the animation sequence of the character is generated on a real-time
basis and approximates human speech. The animated character is capable of
15 expressing certain predetermined states of mind such as happy, angry and
surprised. In addition, the animated character is also capable of approximating
natural movements associated with speech

U.S. Patent 5,901,329 issued on May 4, 1999 by Kito, entitled, "Data processing
20 terminal which determines a type of an external device" discloses a data
processing terminal capable of determining the type of an external device such
as a bar code reader connected thereto and of converting a control command in
a predetermined format into one in another format, so that the data processing
terminal can employ a single program to control bar code readers which use
25 different command systems.

All of the above formats and devices open up a device based communication
network. The lack of web addresses that can fairly relay ones element of
character or service could be fixed if all said prior art worked together on a
30 system designed for the use of imagery as addresses.

There is a strong need for an addressing system that is recognized by machine, as well as by most humans. There is a strong need for a new gateway for images and media to be addressed on a computer and communication network.

5 The addressing system today does not provide full use of name space. Image space is a missing link for all said inventions to work simultaneously and harmoniously.

10 There is an increasing need to offer other alternatives of recognition to help remember an online destination. Accordingly, in light of the above, there is a strong need in the art for a method, product, and apparatus for requesting a resource from an identifier having a character image.

Summary of the Invention

15 In general, in accordance with the present invention a method for requesting a resource from an identifier having a character image includes the steps of generating a first uniform resource identifier (URI) from the character image, wherein the first URI can locate the resource, and requesting the resource from
20 the first URI.

In accordance with yet additional aspects of the present invention, a system which implements substantially the same functionality in substantially the same manner as the methods described above is provided.

25 In accordance with other additional aspects of the present invention, a computer-readable medium that includes computer-executable instructions may be used to perform substantially the same methods as those described above is provided.

30

The foregoing and other features of the invention are hereinafter fully described and particularly pointed out in the claims. The following description and the annexed drawings set forth in detail one or more illustrative aspects of the invention, such being indicative, however, of but one or a few of the various ways in which the principles of the invention may be employed.

Brief Description of the Drawings

Fig. 1 is an illustration of a distributed computer system in accordance with the present invention.

Fig. 2 is an illustration of a base character image surrounded by five different kinds of character modifiers within a given scheme.

Fig. 3 is an illustration of four different character modifiers within the scheme in Fig. 2.

Fig. 4 is a detailed illustration showing a series of reference points for the first four character modifiers in association with a fifth character modifier within the scheme in Fig. 2.

Fig. 5 is a detailed illustration showing a series of reference points for the fifth character modifiers within the scheme in Fig 2.

Fig.6 is an illustration of the regions for the character modifiers within the scheme in Fig 2.

Fig. 7 is a detailed view of two different base character images.

Fig. 8 is an illustration showing the placement and the sequence of the character modifiers that encode a base character image into a translatable image with in the scheme of Fig. 2.

Fig. 9 is an illustration showing the numerical values of the character modifiers used to encode base character images into a translatable image with in the scheme of Fig. 2.

5

Fig. 10 illustrates devices for translation of a Character Image into an address.

Fig.11 is a flow chart showing how to encode a character image.

10 Fig.12 is a flow chart showing how to decode a character image.

Fig.13 is an example of a domain name on the worldwide web that is a base character image.

15 Fig.14 is illustrations of multi-addressed modified character images.

Fig.15 illustrates a modified character image with multiple addresses comprised within one image

Detailed Description of the Invention

20 The present invention will now be described with reference to the drawings, wherein like reference numerals are used to refer to like elements throughout.

Turning first to the nomenclature of the specification, the detailed description which follows is represented largely in terms of processes and symbolic representations of operations by conventional computer components, including a
25 local processing unit, memory storage devices for the local processing unit, display devices, and input devices. Furthermore, these processes and operations may utilize conventional computer components in a heterogeneous distributed computing environment, including remote file servers, computer
30 servers, and memory storage devices. Each of these conventional distributed

computing components is accessible to the local processing unit by a communication network.

The processes and operations performed by the computer include the
5 manipulation of data bits by a local processing unit or remote server and the
maintenance of these bits within data structures resident in one or more of the
local or remote memory storage devices. These data structures impose a
physical organization upon the collection of data bits stored within a memory
storage device and represent specific electrical or magnetic elements. Symbolic
10 representations are the means used by those skilled in the art of computer
programming and computer construction to most effectively convey teachings
and discoveries to others skilled in the art.

For the purposes of this discussion, a process is generally defined as being a
15 sequence of computer-executed steps leading to a desired result. These steps
generally require physical manipulations of physical quantities. Usually, though
not necessarily, these quantities take the form of electrical, magnetic, or optical
signals capable of being stored, transferred, combined, compared, or otherwise
manipulated. It is conventional for those skilled in the art to refer to these
20 signals as bits, bytes, pixel values, words, values, elements, symbols,
characters, terms, numbers, points, records, objects, images, files, directories,
subdirectories, or the like. It should be kept in mind, however, that these and
similar terms should be associated with appropriate physical quantities for
computer operations, and that these terms are merely conventional labels
25 applied to physical quantities that exist within and during operation of the
computer.

It should also be understood that manipulations within the computer are often
referred to in terms such as adding, comparing, moving, positioning, placing,
30 illuminating, removing, altering, etc., which are often associated with manual
operations performed by a human operator. The operations described herein

are machine operations performed in conjunction with various input provided by a human operator or user that interacts with the computer. The machines used for performing the operation of the present invention include local or remote general-purpose digital computers or other similar computing devices including
5 telephones.

In addition, it should be understood that the programs, processes, method, etc. described herein are not related or limited to any particular computer or apparatus nor are they related or limited to any particular communication
10 network architecture. Rather, various types of general-purpose machines may be used with program modules constructed in accordance with the teachings described herein. Similarly, it may prove advantageous to construct a specialized apparatus to perform the method steps described herein by way of dedicated computer systems in a specific network architecture with hard-wired
15 logic or programs stored in nonvolatile memory, such as read only memory.

Fig. 1 shows a distributed computer system 100. The distributed system 100 includes client computers or any network access apparatus 110 connected to server computers 120 via a network 130. The network 130 can use Internet
20 communications protocols (IP) to allow the clients 110 to communicate with the servers 120. The network access apparatus 110 further includes a modem or like transceiver to communicate with the electronic network 130. The modem can communicate with the electronic network 130 via a line such as a telephone line, an ISDN line, a coaxial line, a cable television line, a fiber optic line, or a
25 communication network line. Alternatively, the modem can wirelessly communicate with the electronic network 130. The electronic network 130 can be provided by an on-line service, an Internet service provider, a local area network service, a wide area network service, a cable television service, a wireless data service, an intranet, a satellite service, or the like.

30

The client computers 110 can be any network access apparatus including hand held devices, palmtop computers, personal digital assistants (PDAs), notebook, laptop, portable computers, desktop PCs, workstations, or larger or smaller computer systems. It is noted that the network access apparatus can have a variety of forms, including but not limited to, a general purpose computer, a
5 network computer, a network television, an internet television, a set top box, a web-enabled telephone, an internet appliance, a portable wireless device, a television receiver, a game player, a video recorder, or an audio component.

10 Each client 110 typically includes one or more processors, memories, and input/output devices. An input device can be any suitable device for the user to give input to client computer 110; for example: a keyboard, a 10-key pad, a telephone key pad, a light pen or any pen pointing device, a touchscreen, a button, a dial, a joystick, a steering wheel, a foot pedal, a mouse, a trackball, an
15 optical or magnetic recognition unit such as a bar code or magnetic swipe reader, scanner, a voice, speech or music recognition unit, remote control attached via cable or wireless link to a game set, television, or cable box, a stencil that fits over a computerized drawing tablet, screen capture recognition in a multi-formatted environment. A data glove, an eye-tracking device, or any
20 MIDI device could also be used. A display device could be any suitable output device, such as a display screen, text-to-speech converter, printer, plotter, fax, television set, video telephone, or audio player. Although the input device is typically separate from the display device, they could be combined; for example: a display with an integrated touchscreen, a display with an integrated keyboard,
25 or a speech-recognition unit combined with a text-to-speech converter.

The servers 120 can be similarly configured. However, in many instances server sites 120 include many computers, perhaps connected by a separate private network. In fact, the network 130 may include hundreds of thousands of
30 individual networks of computers. Although the client computers 110 are shown

separate from the server computers 120, it should be understood that a single computer could perform the client and server roles.

During operation of the distributed system 100, users of the clients 110 desire to
5 access information records 122 stored by the servers 120 using, for example,
the World-Wide-Web (WWW), or in short the "Web." The records of information
122 can be in the form of Web pages 150. The pages 150 can be data records
including as content plain textual information, or more complex digitally encoded
multimedia content, such as software programs, graphics, audio signals, videos,
10 and so forth.

It should be understood that although this description focuses on locating
information on the World-Wide-Web, the system can also be used for locating
information via other wide or local area networks (WANs and LANs), or
15 information stored in a single computer using other communications protocols.

The clients 110 can execute Web browser programs 112, such as Netscape
Navigator or MS Internet Explorer to locate the pages or records 150. The
browser programs 112 allow the users to enter addresses of specific Web pages
20 150 to be retrieved. Typically, the address of a Web page is specified as a
Uniform Resource Identifier (URI) or more specifically as a Uniform Resource
Locator (URL). In addition, once a page has been retrieved, the browser
programs 112 can provide access to other pages or records by "clicking" on
hyperlinks to previously retrieved Web pages. Such hyperlinks provide an
25 automated way to enter the URL of another page, and to retrieve that page.

Fig. 2 In this illustration there are base character images made with the alpha
numeric on a typing keyboard to create a base character image of an emoticon
that is a face. E.g. 8-1, :-). In Figure 2 there are illustrations of character images
30 that are surrounded by twenty character modifiers which in this case take on the
appearance of the facial feature, eyelash follicles, and are detached or attached

to the eyes of the base character image of a face. An eyelash follicle/character modifier can hold many different kinds of distinguishable shaped character modifiers, which in this case take on the appearance of the facial feature eyelashes. There can be more or less or a different kind of eyelash/character modifiers to encode a base character image where the eyelash facial feature would fit in with the base character image that is created when using characters from an ASCII format.

Fig. 3 is an illustration of four different kinds of character modifiers that take on the appearance of eyelashes when extending from a character modifier that is a hair follicle. An eyelash/character modifier is a line or a mark extending from a hair follicle/character modifier that is surrounding an eyelid on the eye of a base character image of a face.

Four different kinds of eyelash/character modifiers are one thin short eyelash/character modifier, one thin long eyelash/character modifier, one thick short eyelash/character modifier and one thick long eyelash/character modifier.

A short eyelash/character modifier is no longer then a third of the length of the longest eyelash/character modifier extending from the hair follicle/character modifier that is detached from the eyelid of a base character image of a face.

The thin eyelash/character modifier is no thicker then a half of the thickness of the thickest eyelash/character modifier extending from a hair follicle/character modifier that is detached from the eyelid of a base character image of an eye. There are no more then one eyelash/character modifier per hair follicle/character modifier in the calculated outcome of unique numbers created in this scheme described. More possibilities are possible with added eyelashes per follicle or with a different kind of eyelash all together.

Fig. 4 is an illustration showing why two eyelash/character modifiers are always present. When there is a thick long eyelash/character modifier and a thin short eyelash/character modifier present or a thin long eyelash/character/modifier and a thick short eyelash/character/modifier present. It shows the differentials of height and thickness between eyelash/character modifiers and enables a human or a machine the ability to distinguish what code is present.

Fig. 5 is an illustration of hair follicle/character modifiers. A hair follicle/character modifier is one of twenty tiny circles on an eyelid of a base character image of an eye attached or detached. Fig.5 also depicts how small a hair follicle/character modifier can be. A hair follicle/character modifier can take on any size or shape that can fit in given space surrounding a base character image of an eye and that can be read by a machine. Fig.5 also shows a hair follicle/character modifier can be as large as the base character image will allow. There are twenty hair follicle/character modifiers present surrounding and detached from the eyelids of the base character image of a face. There are five hair follicle/character modifiers per eyelid on the base character image.

Fig.6 is an illustration of four eyelids. An eyelid is the apex of the outer circumference of the top and bottom of the eye in a base character image of a face.

Fig. 7 is an illustration of the eyes, nose and mouth on a base character image of a face.

Fig. 8 is an illustration showing the placement and the sequence of character modifiers that take on the appearance of facial features and encode a base character image.

These character modifier/facial features are placed in a coded sequence that can be humanly read or machine read in a clockwise direction beginning at, the

first hair follicle/character modifier on the far left of the top left eyelid of a base character image to the last hair follicle/character modifier on the far left of the bottom left eyelid of the base character image. The largest empty space between hair follicle/character modifiers is the gap on the left side of the left eye that is between the beginning and end of the designated sequence.

The largest space between hair follicle/character modifiers signifies where the beginning and end is of the encoded base character image. Twenty is the total number of integrals in this encoded base character image of a face.

Fig. 9 is an illustration showing values of the facial feature/character modifiers in this example,

a hair follicle/character modifier equals a zero.

a short thin eyelash/character modifier equals a one.

a long thin eyelash/character modifier equals a two.

a short thick eyelash/character modifier equals a three.

a long thick eyelash/character modifier equals a four.

There are ninety five trillion, three hundred sixty seven billion, four hundred thirty one million, six hundred forty thousand, six hundred and twenty different combinations when this method is used. More possibilities are possible when added character modifiers.

Fig.10 Illustrations of devices and protocol that translate a base character image and a modified base character image to a location on a computer and a communication network.

10-1. In this example a template has a cut out of a base character image and cutouts of eyelash/character modifiers extending from cutouts of hair follicle/character modifiers. This template fits a touch pad attached to a memory storage device, or a piece of paper that can be transferred to a computer via cable and scanner to translate a base character image to an address on a

computer and communication network. The template is a plastic stencil. There are cutouts for eyelash character modifiers. There is a cut out of the base character image. The dimensions of said device could be roughly, two inches by three inches by one eighth of an inch or thinner.

5

10-2. A sound device that is stand alone or integrated with another media device has buttons labeled with character modifiers. When buttons are pressed they play different frequencies or musical notes that can be used to translate character modifier code of a modified character image into an address. An individual can press a sequence of buttons labeled with character modifiers to play frequencies or musical notes into a sound recognizable device hooked up to a computer programmed to translate the frequency based code from a modified base character image and convert it to an address on a computer and communication network, similar to the touch tone telephone. There is a microphone and a speaker and a display that shows the value of said facial code. There is a button that chooses one of the twenty hair follicles. There is an illuminated led display of said facial features. The Dimensions of this device can be roughly three inches by two inches by one half of an inch.

10-3. A character image can be modified to allow an individual to set the unique character modifier sequence using an adjustable type band ink stamp that is capable of printing character image modifier code from and within a mechanism that is able to print to substrate such as paper, wood, metal and others to leave a mark that can be scanned and recognized on a computer and communication network. There are dials used to rotate said facial feature character modifiers. A twist off ink reservoir that attaches to said type band ink stamp. Dials are turned by hand. Memory capabilities within the mechanism can be added with a microprocessor that can translate a modified base character image to a directory location on a computer or communication network.

30

10-4. A graphical interface, on a web page utilizes an Internet browser as a device for translating modified character images into a location on a computer and computer network, using a mouse, keyboard, and other means. This is done by providing twenty boxes that represent character modifiers for the character image in the center of the page. A user is shown through imagery how to operate web page. This is a graphical interface is designed to be understood graphically by one who is savvy of the Internet and not necessarily speaks English. Once understood a user can fill in the twenty boxes and proceed to the location predetermined by modified character image user is seeking. A user can use this form to create a modified base character image also.

10-5. Base character modifier stickers designed for devices that have buttons or pressure sensitive controllers. Telephones, computer keyboards, and remote controls and any other device that can access a database or a communication network and have buttons with preprogrammed functions. These stickers have the legend of the values of a particular scheme that exists within a set of base character image modifiers. These character modifiers can be used to modify and enhance the profile and course of functions these devices possess when communicating with other devices as well as a computer and communication network. When a sticker with a legend to code is appended to a remote control used to control a device one can enter a location one wants to connect with using modified character image. The code illustrated in 10-5 is similar to the code described in Figure 1 through Figure 9. This code puts a number value on hair follicle character modifiers zero through nine exist only on the upper eyelids of a character image of a face. In this scheme there are three different kind of eyelash character modifiers. The shortest eyelash follicle is the first alphanumeric in modified character image. This is followed by the second shortest eyelash character modifier and then the third shortest eyelash character modifier. There are four examples of modified character images and the alphanumeric they translate too. There is also an example of what these stickers would look like on a phone.

10-6. is an illustration on how a base character image can alter the address of an existing recognizable symbol being used for the purpose of arbitrary addressing on a computer and communication network. The first image is an image of an existing symbol used for finding information on a computer and communication network under one format known as barcode recognition. The next illustration shows how this code can be changed to another address on a communication network providing the colon c (:C) is the beginning of a web address. The next image shows other image features that can be associated and recognized with an emoticon that is a web address. Image recognition software recognizes the arms, feet, hat, briefcase and phone that the image shows making it a candidate for an address on a computer information network. The next image shows all the same features as the others except an eyelash code is present also. This emoticon now takes on three addresses. A computer can be programmed to recognize eyelash and follicle character modifiers first and then look for other information to help guide a user of a computer to a more specific location, or too authorize a task for the registration of a particular document or to send a stream of information to a said user or to act as a secondary address to one of the three addresses being displayed within image or eyelash and follicle character modifiers. The imagery could also be a back up address in case recognition of eyelash and follicle character modifiers is not established.

10-7. A flow chart showing how a photograph, drawing, illustration, or file type can be scanned, recognized, translated, and resolved on a computer to get to a directory on a computer and communication network. This is possible when a character image that is an address is present on the media to be scanned. The device used to scan a modified character image, takes that information and sends it through the Internet to a server where a match is looked for. The server sends back any match found.

10-8. Three images showing how modified character images can have sub-directories on a computer as well as upper level directories that are accessible through text recognition as well as image recognition. Recognizable imagery built around a web address, allows a user to add any keywords one wants to ones address to draw focus to the key word along side an image. An upper-level directory next to a modified character can be utilized as well to extend the usage of a modified character image.

10-9 This illustration is similar to that in 10-5 except instead of stickers to direct some one how to dial a telephone, a scanned modified base character image in a telephone number leads to a computer and a communication network when recognized by a scanning device and used with a computer programmed for dialing a phone number and translating the scanned character modifiers to an extension code that leads to a computer and communication network. This illustration shows a regular phone number. Then shows a phone number when you draw attention to a character image that exists within said phone number.

10-10 A flow-chart shows how a piece of mail with a modified base character image points to a real address. A piece of mail bearing a modified character image can aid a postal worker to find the address of said mail from any computer in the world that is hooked up to the Internet. Postal worker scans a modified character image through a scanner which goes through a computer, then onto the Internet and to the base character images server. The address is found in a database existing on server and sent back through the Internet to postal worker.

10-11 . Is an example of how simultaneous broadcast and other media can be an arbitrary address on a communication network when acting as an attachment to a modified base character image that is pre-coded as a broadcast address or a particular media type address on a computer and communication network. A pre-coded modified character image can contain a certain computer command within its modifications that can execute a program in pre-programmed

computerized devices such as a preset human or non-human controlled camera/microphone and any other device capable of recording and distinguishing a signal from a pre-coded modified character image and its surroundings while in scan recognition mode at a single or multiple locations.

5

A pre-coded command could consist of a particular image or a series of led lights set up around the facial features of a character image. These led lights could flash a signal that can be picked up by cameras/microphones and or other sensors on the network alert and ready to pick up a pre-coded modified base character image signal that exists in the real world or a virtual world. A signal is sent through the Internet to a server programmed to detect and retrieve said command from device transmitting pre-coded modified character image.

A server then records pre-coded modified character image along with all information surrounding pre-coded modified character image and stores it on server hard drive. Server then analyzes and separates all machine recognizable formats and makes it ready for a query in a variety of formats on a computer and a communication network. Query consists of a particular modified character image or the information surrounding a modified character image. Query is made through a computer which is on the Internet. Query is detected through server and information is extracted from server, and any match is sent back to origin of query.

Once a client reaches the results of a query, a preprogrammed guide existing visually in a real or virtual environment comprised of modified character images in the form of an animation could project itself through a clients computer reflecting emotion and imagery toward the content of someone's web page. Each projection or any frame of said projection can be its own modified character image address, which would point to another location on a computer and communication network.

Using streaming modified character images is a language recognizable and accessible through out the whole world. A language of modified character imagery is translatable as each word is in the dictionary. A language of emotions that is recognized by human beings when visualized or felt in some way by a human or non-human species can be assigned an image that exists as a location on a computer and communication network. A sentence can be translated into an animation that is fully definable online in any language, because the imagery and emotions that emulate these words are the same as the definitions in most cases. Descriptions of said modified character imagery could exist in all languages at the location of these modified character images online.

Fig. 11.is a flow chart showing the method of encoding a base character image. Too encode a character image with facial features and other information associated with it one would need to go to a character image that is a domain name on the Internet using an Internet browser. At this location there is a blank palette with a choice of base character image schemes one can use to create their own unique modified character image/address. Pre-made character modifiers exist for the choosing as well as a series of online paint tools and multi-lingual text tools is available. One can use these tools to create their address or multiple addresses on a computer and communication network. An address can also be created by just inputting the numeric value of said modification values to character image.

After a modified character image is chosen it is assigned its numeric address by pressing the "create" button like illustrated in fig. 10-4. A unique address is created and ones online existence management options exist as well as templates for creating an online presence. A client can also check other databases on the Internet for the registration of other information.

If any queries for a modified character image is unavailable, a visible prompt consisting of a try again window, would allow a user to change ones modified character image address.

5

Fig 12 Is a flow chart showing the method of Decoding. To decode a modified character image one must enter it from a machine which has character image storage capabilities. The stored information would go through a computer that is on the Internet to a web page on a server with a character image as a domain name. Once at character image named web page, prompts exist guiding a user in uploading and entering the modified character images information too server. Server checks information for follicle character modifiers first. If follicle character modifiers exist, server will check for any other attached media and if any precoded commands exist within the modified character image. If follicle character modifiers do not exist, a match for any media attached to a character image will be determined. After determining what to do server will authorize and send the results through server on to the Internet into a users computer and then presented through a web browser or any device able to translate the protocol necessary for communication on a computer and communication network.

20

Fig.13 Is an example of a domain name on the worldwide web that is a base character image of an earthworm. The 8-1 is the face and head of the earthworm and the .com is the body of the earthworm. The eyes, nose and mouth of the said face are comprised of ASCII text font face style called century gothic. The four other examples in 132 are custom styled ASCII text fonts I designed myself. These fonts can be loaded on any computer for the task of producing and recognizing as ASCII text.

Once a modified character image is converted to a font it is then a candidate for character recognition along with image recognition making it recognizable as indicia for addressing under multiple formats.

- 5 Fig.14 Illustrates character images and modified character images coded with an address. There is a row of seven character images. There is a winking smiley face base character image constructed from the ASCII text of a typing keyboard comprising the semi-colon key and the close parenthesis key. ;) is not recognizable as a domain name on the Internet. It is possible that one day
- 10 Internet addresses can contain punctuations.

- B-7 and 0-8 are Internet web addresses when next to a .com. There is a row of seven modified character images that are unique and can be unique addresses on the Internet when a base character image that exists within it is a domain name on a computer and communication network and can be recognized as a
- 15 character image by a machine that will recognize it along with recognizing any other machine recognizable media.

- Fig.15 Illustrates a modified character image with multiple addresses comprised within one image. The image is two people on a boat in Venice Italy. One person is pushing the boat with a long pole that is going down into the water. The other person is holding a camera pointing out at us the viewers. When the image is scanned and sent to a computer programmed to first find the specific text that comprises a character image the results would point to the 8-1.com you
- 20 see in the picture. This is the first address. This said computer that controlled the program to search for said text can then search for facial features around said pre-defined character image.
- 25

- Once facial features are found a programmed computer can associate the
- 30 designated address to said programmed computer scanning the image. If there are no other pre-destined machine-readable codes within said image the

address would be already resolved. In this particular image there are more addresses. There are three bar codes. The bar-code lays horizontally and takes on the appearance of venetian blinds in a window over looking a water canal, as well as taking on the appearance of a corrugated gates at the entrance of a building right in front of a water canal. Each one of these bar codes can be different locations or the same location as the facial features on a computer and communication network. When barcode takes on the same address it is acting as an alternative measure for the secure delivery to an address through machine recognition. After a computer programmed to find these formats have found all these formats it would have a background image left over. Background image is recognizable as an image in an image retrieval database also. This creates another valid address for a programmed computer to follow.

Using this system with today's technology will allow an almost infinite amount of addresses that could also be described as more then the maximum possible on a computer system based on pixels, nodes and directory configuration as well as storage capabilities because the imagination one can use to create an address is most definitely infinite using this said system.

Although the invention has been shown and described with respect to a certain preferred aspect or aspects, it is obvious that equivalent alterations and modifications will occur to others skilled in the art upon the reading and understanding of this specification and the annexed drawings. In particular regard to the various functions performed by the above described items referred to by numerals (components, assemblies, devices, compositions, etc.), the terms (including a reference to a "means") used to describe such items are intended to correspond, unless otherwise indicated, to any item which performs the specified function of the described item (e.g., that is functionally equivalent), even though not structurally equivalent to the disclosed structure which performs the function in the herein illustrated exemplary aspect or aspects of the invention. In addition, while a particular feature of the invention may have been described

above with respect to only one of several illustrated aspects, such feature may be combined with one or more other features of the other aspects, as may be desired and advantageous for any given or particular application.

5 The description herein with reference to the figures will be understood to describe the present invention in sufficient detail to enable one skilled in the art to utilize the present invention in a variety of applications and devices. It will be readily apparent that various changes and modifications could be made therein without departing from the spirit and scope of the invention as defined in the
10 following claims.

FIG. 1
FIG. 2
FIG. 3
FIG. 4
FIG. 5
FIG. 6
FIG. 7
FIG. 8
FIG. 9
FIG. 10
FIG. 11
FIG. 12
FIG. 13
FIG. 14
FIG. 15
FIG. 16
FIG. 17
FIG. 18
FIG. 19
FIG. 20
FIG. 21
FIG. 22
FIG. 23
FIG. 24
FIG. 25
FIG. 26
FIG. 27
FIG. 28
FIG. 29
FIG. 30
FIG. 31
FIG. 32
FIG. 33
FIG. 34
FIG. 35
FIG. 36
FIG. 37
FIG. 38
FIG. 39
FIG. 40
FIG. 41
FIG. 42
FIG. 43
FIG. 44
FIG. 45
FIG. 46
FIG. 47
FIG. 48
FIG. 49
FIG. 50
FIG. 51
FIG. 52
FIG. 53
FIG. 54
FIG. 55
FIG. 56
FIG. 57
FIG. 58
FIG. 59
FIG. 60
FIG. 61
FIG. 62
FIG. 63
FIG. 64
FIG. 65
FIG. 66
FIG. 67
FIG. 68
FIG. 69
FIG. 70
FIG. 71
FIG. 72
FIG. 73
FIG. 74
FIG. 75
FIG. 76
FIG. 77
FIG. 78
FIG. 79
FIG. 80
FIG. 81
FIG. 82
FIG. 83
FIG. 84
FIG. 85
FIG. 86
FIG. 87
FIG. 88
FIG. 89
FIG. 90
FIG. 91
FIG. 92
FIG. 93
FIG. 94
FIG. 95
FIG. 96
FIG. 97
FIG. 98
FIG. 99
FIG. 100
FIG. 101
FIG. 102
FIG. 103
FIG. 104
FIG. 105
FIG. 106
FIG. 107
FIG. 108
FIG. 109
FIG. 110
FIG. 111
FIG. 112
FIG. 113
FIG. 114
FIG. 115
FIG. 116
FIG. 117
FIG. 118
FIG. 119
FIG. 120
FIG. 121
FIG. 122
FIG. 123
FIG. 124
FIG. 125
FIG. 126
FIG. 127
FIG. 128
FIG. 129
FIG. 130
FIG. 131
FIG. 132
FIG. 133
FIG. 134
FIG. 135
FIG. 136
FIG. 137
FIG. 138
FIG. 139
FIG. 140
FIG. 141
FIG. 142
FIG. 143
FIG. 144
FIG. 145
FIG. 146
FIG. 147
FIG. 148
FIG. 149
FIG. 150
FIG. 151
FIG. 152
FIG. 153
FIG. 154
FIG. 155
FIG. 156
FIG. 157
FIG. 158
FIG. 159
FIG. 160
FIG. 161
FIG. 162
FIG. 163
FIG. 164
FIG. 165
FIG. 166
FIG. 167
FIG. 168
FIG. 169
FIG. 170
FIG. 171
FIG. 172
FIG. 173
FIG. 174
FIG. 175
FIG. 176
FIG. 177
FIG. 178
FIG. 179
FIG. 180
FIG. 181
FIG. 182
FIG. 183
FIG. 184
FIG. 185
FIG. 186
FIG. 187
FIG. 188
FIG. 189
FIG. 190
FIG. 191
FIG. 192
FIG. 193
FIG. 194
FIG. 195
FIG. 196
FIG. 197
FIG. 198
FIG. 199
FIG. 200
FIG. 201
FIG. 202
FIG. 203
FIG. 204
FIG. 205
FIG. 206
FIG. 207
FIG. 208
FIG. 209
FIG. 210
FIG. 211
FIG. 212
FIG. 213
FIG. 214
FIG. 215
FIG. 216
FIG. 217
FIG. 218
FIG. 219
FIG. 220
FIG. 221
FIG. 222
FIG. 223
FIG. 224
FIG. 225
FIG. 226
FIG. 227
FIG. 228
FIG. 229
FIG. 230
FIG. 231
FIG. 232
FIG. 233
FIG. 234
FIG. 235
FIG. 236
FIG. 237
FIG. 238
FIG. 239
FIG. 240
FIG. 241
FIG. 242
FIG. 243
FIG. 244
FIG. 245
FIG. 246
FIG. 247
FIG. 248
FIG. 249
FIG. 250
FIG. 251
FIG. 252
FIG. 253
FIG. 254
FIG. 255
FIG. 256
FIG. 257
FIG. 258
FIG. 259
FIG. 260
FIG. 261
FIG. 262
FIG. 263
FIG. 264
FIG. 265
FIG. 266
FIG. 267
FIG. 268
FIG. 269
FIG. 270
FIG. 271
FIG. 272
FIG. 273
FIG. 274
FIG. 275
FIG. 276
FIG. 277
FIG. 278
FIG. 279
FIG. 280
FIG. 281
FIG. 282
FIG. 283
FIG. 284
FIG. 285
FIG. 286
FIG. 287
FIG. 288
FIG. 289
FIG. 290
FIG. 291
FIG. 292
FIG. 293
FIG. 294
FIG. 295
FIG. 296
FIG. 297
FIG. 298
FIG. 299
FIG. 300
FIG. 301
FIG. 302
FIG. 303
FIG. 304
FIG. 305
FIG. 306
FIG. 307
FIG. 308
FIG. 309
FIG. 310
FIG. 311
FIG. 312
FIG. 313
FIG. 314
FIG. 315
FIG. 316
FIG. 317
FIG. 318
FIG. 319
FIG. 320
FIG. 321
FIG. 322
FIG. 323
FIG. 324
FIG. 325
FIG. 326
FIG. 327
FIG. 328
FIG. 329
FIG. 330
FIG. 331
FIG. 332
FIG. 333
FIG. 334
FIG. 335
FIG. 336
FIG. 337
FIG. 338
FIG. 339
FIG. 340
FIG. 341
FIG. 342
FIG. 343
FIG. 344
FIG. 345
FIG. 346
FIG. 347
FIG. 348
FIG. 349
FIG. 350
FIG. 351
FIG. 352
FIG. 353
FIG. 354
FIG. 355
FIG. 356
FIG. 357
FIG. 358
FIG. 359
FIG. 360
FIG. 361
FIG. 362
FIG. 363
FIG. 364
FIG. 365
FIG. 366
FIG. 367
FIG. 368
FIG. 369
FIG. 370
FIG. 371
FIG. 372
FIG. 373
FIG. 374
FIG. 375
FIG. 376
FIG. 377
FIG. 378
FIG. 379
FIG. 380
FIG. 381
FIG. 382
FIG. 383
FIG. 384
FIG. 385
FIG. 386
FIG. 387
FIG. 388
FIG. 389
FIG. 390
FIG. 391
FIG. 392
FIG. 393
FIG. 394
FIG. 395
FIG. 396
FIG. 397
FIG. 398
FIG. 399
FIG. 400
FIG. 401
FIG. 402
FIG. 403
FIG. 404
FIG. 405
FIG. 406
FIG. 407
FIG. 408
FIG. 409
FIG. 410
FIG. 411
FIG. 412
FIG. 413
FIG. 414
FIG. 415
FIG. 416
FIG. 417
FIG. 418
FIG. 419
FIG. 420
FIG. 421
FIG. 422
FIG. 423
FIG. 424
FIG. 425
FIG. 426
FIG. 427
FIG. 428
FIG. 429
FIG. 430
FIG. 431
FIG. 432
FIG. 433
FIG. 434
FIG. 435
FIG. 436
FIG. 437
FIG. 438
FIG. 439
FIG. 440
FIG. 441
FIG. 442
FIG. 443
FIG. 444
FIG. 445
FIG. 446
FIG. 447
FIG. 448
FIG. 449
FIG. 450
FIG. 451
FIG. 452
FIG. 453
FIG. 454
FIG. 455
FIG. 456
FIG. 457
FIG. 458
FIG. 459
FIG. 460
FIG. 461
FIG. 462
FIG. 463
FIG. 464
FIG. 465
FIG. 466
FIG. 467
FIG. 468
FIG. 469
FIG. 470
FIG. 471
FIG. 472
FIG. 473
FIG. 474
FIG. 475
FIG. 476
FIG. 477
FIG. 478
FIG. 479
FIG. 480
FIG. 481
FIG. 482
FIG. 483
FIG. 484
FIG. 485
FIG. 486
FIG. 487
FIG. 488
FIG. 489
FIG. 490
FIG. 491
FIG. 492
FIG. 493
FIG. 494
FIG. 495
FIG. 496
FIG. 497
FIG. 498
FIG. 499
FIG. 500
FIG. 501
FIG. 502
FIG. 503
FIG. 504
FIG. 505
FIG. 506
FIG. 507
FIG. 508
FIG. 509
FIG. 510
FIG. 511
FIG. 512
FIG. 513
FIG. 514
FIG. 515
FIG. 516
FIG. 517
FIG. 518
FIG. 519
FIG. 520
FIG. 521
FIG. 522
FIG. 523
FIG. 524
FIG. 525
FIG. 526
FIG. 527
FIG. 528
FIG. 529
FIG. 530
FIG. 531
FIG. 532
FIG. 533
FIG. 534
FIG. 535
FIG. 536
FIG. 537
FIG. 538
FIG. 539
FIG. 540
FIG. 541
FIG. 542
FIG. 543
FIG. 544
FIG. 545
FIG. 546
FIG. 547
FIG. 548
FIG. 549
FIG. 550
FIG. 551
FIG. 552
FIG. 553
FIG. 554
FIG. 555
FIG. 556
FIG. 557
FIG. 558
FIG. 559
FIG. 560
FIG. 561
FIG. 562
FIG. 563
FIG. 564
FIG. 565
FIG. 566
FIG. 567
FIG. 568
FIG. 569
FIG. 570
FIG. 571
FIG. 572
FIG. 573
FIG. 574
FIG. 575
FIG. 576
FIG. 577
FIG. 578
FIG. 579
FIG. 580
FIG. 581
FIG. 582
FIG. 583
FIG. 584
FIG. 585
FIG. 586
FIG. 587
FIG. 588
FIG. 589
FIG. 590
FIG. 591
FIG. 592
FIG. 593
FIG. 594
FIG. 595
FIG. 596
FIG. 597
FIG. 598
FIG. 599
FIG. 600
FIG. 601
FIG. 602
FIG. 603
FIG. 604
FIG. 605
FIG. 606
FIG. 607
FIG. 608
FIG. 609
FIG. 610
FIG. 611
FIG. 612
FIG. 613
FIG. 614
FIG. 615
FIG. 616
FIG. 617
FIG. 618
FIG. 619
FIG. 620
FIG. 621
FIG. 622
FIG. 623
FIG. 624
FIG. 625
FIG. 626
FIG. 627
FIG. 628
FIG. 629
FIG. 630
FIG. 631
FIG. 632
FIG. 633
FIG. 634
FIG. 635
FIG. 636
FIG. 637
FIG. 638
FIG. 639
FIG. 640
FIG. 641
FIG. 642
FIG. 643
FIG. 644
FIG. 645
FIG. 646
FIG. 647
FIG. 648
FIG. 649
FIG. 650
FIG. 651
FIG. 652
FIG. 653
FIG. 654
FIG. 655
FIG. 656
FIG. 657
FIG. 658
FIG. 659
FIG. 660
FIG. 661
FIG. 662
FIG. 663
FIG. 664
FIG. 665
FIG. 666
FIG. 667
FIG. 668
FIG. 669
FIG. 670
FIG. 671
FIG. 672
FIG. 673
FIG. 674
FIG. 675
FIG. 676
FIG. 677
FIG. 678
FIG. 679
FIG. 680
FIG. 681
FIG. 682
FIG. 683
FIG. 684
FIG. 685
FIG. 686
FIG. 687
FIG. 688
FIG. 689
FIG. 690
FIG. 691
FIG. 692
FIG. 693
FIG. 694
FIG. 695
FIG. 696
FIG. 697
FIG. 698
FIG. 699
FIG. 700
FIG. 701
FIG. 702
FIG. 703
FIG. 704
FIG. 705
FIG. 706
FIG. 707
FIG. 708
FIG. 709
FIG. 710
FIG. 711
FIG. 712
FIG. 713
FIG. 714
FIG. 715
FIG. 716
FIG. 717
FIG. 718
FIG. 719
FIG. 720
FIG. 721
FIG. 722
FIG. 723
FIG. 724
FIG. 725
FIG. 726
FIG. 727
FIG. 728
FIG. 729
FIG. 730
FIG. 731
FIG. 732
FIG. 733
FIG. 734
FIG. 735
FIG. 736
FIG. 737
FIG. 738
FIG. 739
FIG. 740
FIG. 741
FIG. 742
FIG. 743
FIG. 744
FIG. 745
FIG. 746
FIG. 747
FIG. 748
FIG. 749
FIG. 750
FIG. 751
FIG. 752
FIG. 753
FIG. 754
FIG. 755
FIG. 756
FIG. 757
FIG. 758
FIG. 759
FIG. 760
FIG. 761
FIG. 762
FIG. 763
FIG. 764
FIG. 765
FIG. 766
FIG. 767
FIG. 768
FIG. 769
FIG. 770
FIG. 771
FIG. 772
FIG. 773
FIG. 774
FIG. 775
FIG. 776
FIG. 777
FIG. 778
FIG. 779
FIG. 780
FIG. 781
FIG. 782
FIG. 783
FIG. 784
FIG. 785
FIG. 786
FIG. 787
FIG. 788
FIG. 789
FIG. 790
FIG. 791
FIG. 792
FIG. 793
FIG. 794
FIG. 795
FIG. 796
FIG. 797
FIG. 798
FIG. 799
FIG. 800
FIG. 801
FIG. 802
FIG. 803
FIG. 804
FIG. 805
FIG. 806
FIG. 807
FIG. 808
FIG. 809
FIG. 810
FIG. 811
FIG. 812
FIG. 813
FIG. 814
FIG. 815
FIG. 816
FIG. 817
FIG. 818
FIG. 819
FIG. 820
FIG. 821
FIG. 822
FIG. 823
FIG. 824
FIG. 825
FIG. 826
FIG. 827
FIG. 828
FIG. 829
FIG. 830
FIG. 831
FIG. 832
FIG. 833
FIG. 834
FIG. 835
FIG. 836
FIG. 837
FIG. 838
FIG. 839
FIG. 840
FIG. 841
FIG. 842
FIG. 843
FIG. 844
FIG. 845
FIG. 846
FIG. 847
FIG. 848
FIG. 849
FIG. 850
FIG. 851
FIG. 852
FIG. 853
FIG. 854
FIG. 855
FIG. 856
FIG. 857
FIG. 858
FIG. 859
FIG. 860
FIG. 861
FIG. 862
FIG. 863
FIG. 864
FIG. 865
FIG. 866
FIG. 867
FIG. 868
FIG. 869
FIG. 870
FIG. 871
FIG. 872
FIG. 873
FIG. 874
FIG. 875
FIG. 876
FIG. 877
FIG. 878
FIG. 879
FIG. 880
FIG. 881
FIG. 882
FIG. 883
FIG. 884
FIG. 885
FIG. 886
FIG. 887
FIG. 888
FIG. 889
FIG. 890
FIG. 891
FIG. 892
FIG. 893
FIG. 894
FIG. 895
FIG. 896
FIG. 897
FIG. 898
FIG. 899
FIG. 900
FIG. 901
FIG. 902
FIG. 903
FIG. 904
FIG. 905
FIG. 906
FIG. 907
FIG. 908
FIG. 909
FIG. 910
FIG. 911
FIG. 912
FIG. 913
FIG. 914
FIG. 915
FIG. 916
FIG. 917
FIG. 918
FIG. 919
FIG. 920
FIG. 921
FIG. 922
FIG. 923
FIG. 924
FIG. 925
FIG. 926
FIG. 927
FIG. 928
FIG. 929
FIG. 930
FIG. 931
FIG. 932
FIG. 933
FIG. 934
FIG. 935
FIG. 936
FIG. 937
FIG. 938
FIG. 939
FIG. 940
FIG. 941
FIG. 942
FIG. 943
FIG. 944
FIG. 945
FIG. 946
FIG. 947
FIG. 948
FIG. 949
FIG. 950
FIG. 951
FIG. 952
FIG. 953
FIG. 954
FIG. 955
FIG. 956
FIG. 957
FIG. 958
FIG. 959
FIG. 960
FIG. 961
FIG. 962
FIG. 963
FIG. 964
FIG. 965
FIG. 966
FIG. 967
FIG. 968
FIG. 969
FIG. 970
FIG. 971
FIG. 972
FIG. 973
FIG. 974
FIG. 975
FIG. 976
FIG. 977
FIG. 978
FIG. 979
FIG. 980
FIG. 981
FIG. 982
FIG. 983
FIG. 984
FIG. 985
FIG. 986
FIG. 987
FIG. 988
FIG. 989
FIG. 990
FIG. 991
FIG. 992
FIG. 993
FIG. 994
FIG. 995
FIG. 996
FIG. 997
FIG. 998
FIG. 999
FIG. 1000

15

20

25

30